

DATASHEET F-201CV

EL-FLOW Select F-201CV

Digital Thermal Mass Flow Controller for Gases



Gas Mass Flow Controllers for low flow rates

Bronkhorst® model F-201CV Mass Flow Controllers (MFCs) are suited for accurate measurement and control of flow ranges between 0,16...8 ml_n/min and 0,5...25 l_n/min at operating pressures between vacuum and 64 bar. The MFC consists of a thermal mass flow sensor, a precise control valve and a microprocessor based pc-board with signal and fieldbus conversion. As a function of a setpoint value, the flow controller swiftly adjusts the desired flow rate.

EL-FLOW® Select series are equipped with a digital pc-board, offering high accuracy, excellent temperature stability and fast response. The main digital pc-board contains all of the general functions needed for measurement and control. In addition to the standard RS232 output the instruments also offer analog I/O. As an option, an on-board interface can be mounted to provide CANopen®, DeviceNet™, EtherCAT®, PROFIBUS DP, PROFINET, Modbus RTU, ASCII or TCP/IP, EtherNet/IP, POWERLINK or FLOW-BUS protocols. The EL-FLOW® Select design features optional Multi Gas / Multi Range functionality, providing (OEM-) customers with optimal flexibility and process efficiency.

Technical specifications

Measurement / control system

Flow range (intermediate ranges available)	min. 0,16...8 ml _n /min max. 0,5...25 l _n /min (based on N ₂)
Accuracy (incl. linearity) (based on actual calibration)	± 0,5 % RD plus ±0,1%FS
Repeatability	< 0,2 % RD
Turndown ratio	up to 1:187,5 (1:50 in analog mode)
Multi fluid capability	storage of max. 8 calibration curves; optional Multi Gas / Multi Range functionality up to 10 bar abs
Settling time (in control, typical)	standard: 1...2 seconds option: down to 500 msec
Control stability	< ± 0,1 % FS (typical for 1 l _n /min N ₂)
Operating temperature	-10 ... +70 °C
Temperature sensitivity	zero: < 0,05% FS/°C; span: < 0,05% Rd/°C
Pressure sensitivity	< 0,1% Rd/bar typical N ₂ ; 0,01% Rd/bar typical H ₂
Max. Kv-value	6,6 x 10 ⁻²
Leak integrity, outboard	tested < 2 x 10 ⁻⁹ mbar l/s He
Attitude sensitivity	max. error at 90° off horizontal 0,2% at 1 bar, typical N ₂
Warm-up time	30 min. for optimum accuracy 2 min. for accuracy ± 2% FS

Mechanical parts

Material (wetted parts)	Stainless steel 316L or comparable			
Pressure rating (PN)	64 bar abs			
Process connections	compression type or face seal (VCR/VCO) couplings			
Seals	standard: Viton®; options: EPDM, Kalrez® (FFKM), FDA and USP Class VI approved compounds			
Weight	0,6 kg			
Ingress protection	IP40			

Electrical properties

Power supply	+15 ... 24 Vdc			
Max. power consumption	Supply	at voltage I/O	at current I/O	extra for fieldbus
	15 V	290 mA	320 mA	<75 mA
	24 V	200 mA	215 mA	<50 mA
Analog output	0...5 (10) Vdc or 0 (4)...20 mA (sourcing output)			
Digital communication	standard: RS232; options: PROFIBUS DP, CANopen®, DeviceNet™, PROFINET, EtherCAT®, Modbus RTU, ASCII or TCP/IP, EtherNet/IP, POWERLINK, FLOW-BUS			

Electrical connection

Analog/RS232	9-pin D-connector (male);
PROFIBUS DP	bus: 9-pin D-connector (female); power: 9-pin D-connector (male);
CANopen® / DeviceNet™	5-pin M12-connector (male);
FLOW-BUS/Modbus-RTU/ASCII	RJ45 modular jack
Modbus TCP / EtherNet/IP / POWERLINK	2 x RJ45 modular jack (in/out);
EtherCAT®/ PROFINET	2 x RJ45 modular jack (in/out)

Control valve options

External actuator options to be connected to the controller

Ex-proof specifications

Approvals / certificates

Technical specifications subject to change without notice.

For dimensional drawings and hook-up diagrams please visit the [product page](#) on our [website](#)

Recommended accessories



E-8000 SERIES
DIGITAL READOUT /
CONTROL SYSTEMS

Digital Readout / Control
Systems

Bright, wide angle, 1.8"
display (TFT technology)
User friendly operation,
menu driven with 4 push
buttons



BRIGHT SERIES
COMPACT LOCAL R/C
MODULE

Compact Local R/C Module

Bright, wide angle, 1.8"
display
User friendly operation
Indication/operation/configuration



PIPS SERIES

Plug-in Power Supply

For lab-style or industrial
devices
Interchangeable plugs
(Euro, UK, USA, Australian,
IEC) for mains connection



IN-LINE FILTER
LOW FLOW SERIE M-
411 RS

1/4" female in / male out
100 bar
Average porosity 0.5...15
µm

Related products



EL-FLOW SELECT F-200CV

Min. flow 0,014...0,7
mln/min
Max. flow 0,18...9 mln/min
Pressure rating 64 bar
Compact design
High accuracy and
repeatability



EL-FLOW SELECT F-211CV

Min. flow 0,16...8 mln/min
Max. flow 0,5...25 lln/min
Pressure rating 100 bar
Compact design
High accuracy and
repeatability



EL-FLOW SELECT F-201AV

Min. flow 0,4...20 lln/min
Max. flow 0,6...100 lln/min
Pressure rating 64 bar
Compact design
High accuracy and
repeatability



EL-FLOW SELECT F-111B

Min. flow 0,16...8 mln/min
Max. flow 0,16...25 lln/min
Pressure rating 100 bar
Compact design
High accuracy



BRONKHORST USA LLC

57 South Commerce Way

Suite 120

USA - Bethlehem, PA 18017

Tel. +1-610-866-6750

sales@bronkhorstusa.com

